



Light, metal-free safety shoe with composite toe cap, textile nail protection, and PU grip outsole.

jalas[®] 6488

ASTM F2413-24 M/I/C/SD 35/PR EN ISO 20345:2022 S3S, SR, FO, SC, LG



Learn more

ALL METAL FREE SAFETY SHOE

The JALAS 6488 is a lightweight, metal-free safety shoe for environments requiring metal-free equipment, but suitable for others as well. It features a composite toe cap, durable PU pro-nose and flexible textile nail penetration insert for superior safety. The upper is made from water-repellent split leather and PU-coated leather, certified by LWG. The high-grip PU outsole ensures stability, while shock-absorbing Poron[®] XRD[®] insoles provide all-day comfort.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Oil-resistant outsole
- Metal free
- Anti-static properties
- Pull loops
- Water repellent
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)



PREVENTS RISK OF

Toe injuries, Nail penetration, Antistatic, Contact with cold

PRIMARY AREAS OF USE

Airport work, Repair work, Service work, Transport work, Warehouse work

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

NAIL PROTECTION MATERIAL EcoFlex Zero perforation textile

FITTING Narrow/Regular

UPPER MATERIAL PU-coated leather, Split leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyester, polyamide

INSOLE JALAS 8303 FX3 Supreme

OUTSOLE MATERIAL PU outsole

FASTENING Laces

SHOELACES LENGTH 130 cm

COLOUR Black

NET WEIGHT, (SIZE 42) 1.3 kg

COMPLIANCE



TP TC 019:2011



ASTM F2413-24
M/I/C/SD 35/PR



EN ISO 20345:2022
S3S, SR, FO, SC, LG



DGVU 112-191

FEATURES



Composite toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Anti-static properties



ESD

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	6488-36	6408487575181
37	4	5	6	6488-37	6408487575235
38	5	5.5	6.5	6488-38	6408487575280
39	6	6.5	7.5	6488-39	6408487575334
40	6.5	7.5	8.5	6488-40	6408487575389
41	7	8	9	6488-41	6408487575433
42	8	9	10	6488-42	6408487575488
43	9	9.5	11	6488-43	6408487575532
44	10	10.5	11.5	6488-44	6408487575587
45	10.5	11	12.5	6488-45	6408487575631
46	11	12	13	6488-46	6408487575686
47	12	13	14	6488-47	6408487575730

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com